CODE ANALYSIS

	APPLICABLE CODES
	Year Year
-	International Building Code International Mechanical Code International Plumbing Code International Fire Code International Energy Conservation Code International Energy Conservation Code International Energy Conservation Code International Energy Conservation Code International Energy Conservation Code International Energy Conservation Code International Electrical Code Uniform Code for Building Conservation ADA Accessibility Alitical Electrical Code Uniform Code for Building Conservation ADA Accessibility Alitical Electrical Code International Fire Code Interna
	A. Occupancy and Group: B
	Change in Use: Yes NoX Mixed Occupancy: Yes NoX Special Use and Occupancy (e.g. High Rise, Covered Mall):
<	B. Seismic Design Category: D Design Wind Speed: 90 mph
	C. Type of Construction (circle one):
	Image: A construction of the Exterior Walls based on the fire separation distance (in hours): Image: A construction of the Exterior Walls based on the fire separation distance (in hours):
j	North: 0 South: 0 East: 0 West: 0
	E. Mixed Occupancies: Nonseparated Uses:
	F: Sprinklers: EXISTING
	Required: X Provided: X Type of Sprinkler System: WET
	G: Number of Stories: Building Height: 23'-0"
Н	H: Actual Area per Floor (square feet): 29,165
	I: Tabular Area:
	J: Area Modifications: N/A

Fire Resistance Rating	Requirements	for Building	Elements	(hours).
------------------------	--------------	--------------	----------	----------

Element	Hours	Assembly Listing	Element	Hours	Assembly Listing
Exterior Bearing Walls Interior Bearing Walls Exterior Non-Bearing Walls Structural Frame Partitions - Permanent Fire Barriers	0 0 0 0 0		Floors - Ceiling Floors Roofs - Ceiling Roofs Exterior Doors and Windows Shaft Enclosures Fire Walls Fire Partitions Smoke Partitions	0 0 0 0 0	

PROJECT DESCRIPTION

DEMOLITION OF EXISTING ROOFING & FLASHINGS, & MECHANICAL ELEMENTS INDICATED. PROVIDE NEW ROOFING & INSULATION, FLASHINGS &

INDICATED. PROVIDE NEW PRIMARY ROOF DRAINS AS INDICATED, PROVIDE 3 NEW ROOF LADDERS

ROOF CLASSIFICATIONS

SPECIAL INSPECTIONS

NO SPECIAL INSPECTIONS -SEE SECT. 1704.1 IBC

DRAWINGS AND SPECIFICATIONS IN THIS BID SET MEET DFCM STANDARDS FOR RE-ROOFING

Division of Facilities Construction and Management

Phase CONSTRUCTION DOCUMENTS Program P

APPROVAL DOES NOT RELIEVE A/E OF DESIGN LIABILITY

PLAN CHECK

IBC TABLE 1505.1 CLASS "C" REQUIRED

CLASS "A" ROOF PROVIDED

Accessibility

Architectural

Electrical

HVAC

Landscape

Plumbing

Structural

Specification

Civil

RE-SET EXISTING MECHANICAL EQUIPMENT AS

Design Occupant Load: <u>N/A</u> Exit Width Required: N/A Exit Width Provided: N/A

Minimum Number of Required Plumbing Facilities: N/A

a) Water Closets - Required (m) N/A (f) Provided (m) b) Lavatories - Required (m) <u>N/A</u> (f) _____ Provided (m) ____ (f) ____

c) Bath Tubs or Showers: N/A

d) Drinking Fountains: <u>N/A</u> Service Sinks: <u>N/A</u>

FOOTNOTES:

In case of conflict with the U.S. Department of Justice Federal Registers Parts I through **Y** - ADA Guidelines and specific reference to the International Building Code Accessibility Chapters, the more restrictive requirement shall govern.

Additional Code Information shall be provided at the discretion of the Building Official for Complex Buildings. Including, but not limited to:

a) High Rise Requirements.

b) Atriums.

c) Performance Based Criteria. d) Means or Egress Analysis.

e) Fire Assembly Locator Sheet.

f) Exterior and Interior Accessibility Route.

g) Fire Stopping, Including Tested Design Number.

SOUTHERN UTAH UNIVERSITY TECHNICAL BUILDING RE-ROOF CEDAR CITY, UTAH 84720

DFCM PROJECT NUMBER 09257730

CONSULTING ENGINEERS

ARCHITECTURAL

MESA CONSULTING GROUP 53 NORTH MAIN STREET ST. GEORGE, UTAH 84770 (435) 673-4800

STRUCTURAL

MESA CONSULTING GROUP 53 NORTH MAIN STREET ST. GEORGE, UTAH 84770 (435) 673-4800

MECHANICAL & PLUMBING

WHW ENGINEERING INC. 8619 SOUTH SANDY PARKWAY #101 SANDY, UTAH 84070 (801) 466-4021

OWNER INFO

SOUTHERN UTAH UNIVERSITY DIVISION OF FACILITIES CONSTRUCTION & MANAGEMENT 4110 STATE OFFICE BUILDING SALT LAKE CITY, UTAH 84114 MATT BOYER, PROJECT COORDINATOR




State of Utah-Department of Administrative Services

DIVISION OF FACILITIES CONSTRUCTION AND MANAGEMENT 4110 State Office Building/Salt Lake City, Utah 84114/538-3018

SHEET	TITLE
	GENERAL
G101	COVER SHEET
	ARCHITECTURAL
A101	SAFETY EXIT PLAN
A102	COVERED WALK DETAILS
D101	DEMO-EXIST ROOF PLAN
D102	DEMO-ROOF DETAILS
A201	NEW ROOF PLAN
A202	ROOF DETAILS
A203	ROOF DETAILS
A204	ROOF DETAILS
A210	ROOF DRAIN PLAN
	5 DRAWING INDEX


COVER SHEET

G101



SOUTHERN UTAH UNIVERSIT TECH. BUILDING REROOF 351 WEST UNIVERSITY BLVD. CEDAR CITY, UTAH 84720


COVERED **PEDESTRIAN** WALK SAFETY PLAN



SOUTHERN UTAH UNIVERSIT TECH. BUILDING REROOF 351 WEST UNIVERSITY BLVD. CEDAR CITY, UTAH 84720

COVERED WALK

DETAILS



KEYNOTES

AND RESET AS REQUIRED FOR NEW ROOFING


FOR REMOVAL OF OLD ROOFING AND SCREEN MECHANICAL SYSTEM TO WORK PROPERLY.

FOR INSTALATION OF NEW ROOF. WALL TO RE-INSTALL SCREEN AFTER NEW ROOF &

SOUTHERN UTAH UNIVERSIT TECH. BUILDING REROOF 351 WEST UNIVERSITY BLVD. CEDAR CITY, UTAH 84720


DEMO-EXIST ROOF PLAN

D101



DEMO-EXISTING ROOF DETAILS

D102



KEYNOTES

- (1) EXISTING ROOF ACCESS HATCH RAISE CURB AS REQUIRED FOR NEW ROOFING ASSEMBLY (2) ROOF MOUNTED MECHANICAL UNIT TO
- (3) EXISTING ROOF MOUNTED AC UNIT PROVIDE NEW CURB MOUNTING
- (5) EXISTING ROOF LADDER
- 6 2" ROOF DRAIN TO REMAIN, RAISE & PROVIDE EXTENSION PIPING FOR NEW ROOFING ASSEMBLY
- (7) ROOF DRAIN TO REMAIN, RAISE & PROVIDE EXTENSION PIPING FOR NEW ROOFING ASSEMBLY
- (8) EXISTING VENT PIPE, PROVIDE NEW PIPE BOOT AS MFGR REQUIREMENTS
- 9 EXISTING 1/2" ELECTRICAL CONDUIT (SEE
- ELECTRICAL NOTES & SPECIFICATIONS) (10) EXISTING 4" SQUARE ROOF VENT TO REMAIN
- (1) EXISTING 4"X4"X5' METAL A/C COMPRESSOR
- (12) PROVIDE NEW ROOFING BOOT @ CONDUIT
- (13) PROVIDE NEW ROOFING BOOT AT AC LINE SET ROOF PENETRATION
- (14) PROVIDE NEW FLEXIBLE WALKWAY AS SHOWN
- 15 3" ELECTRIC RISER W/ WEATHER CAP AND PITCH POT TO BE REMOVED (16) EXHAUST HOOD
- (17) EXHAUST FAN, RAISE & RESET IF REQD. FOR NEW ROOFING ASSEMBLY
- (18) RELIEF AIR VENTS/HOOD REMOVED, RESET AFTER NEW ROOFING AND SCREEN WALL ARE IN PLACE. PROVIDE ALL CONNECTION & ADJUSTMENTS NECESSARY FOR A PROPERLY FUNCTIONING MECHANICAL SYSTEM
- $^{\prime}$ OFF 2" +- FOR THE NEW ROOFING ASSEMBLY. REPLACE IN EXISTING POSITION (20) NEW ROOF LADDER (SEE DETAIL E1 & E5/A203
- (21) 8" EXHAUSTS PIPE PROVIDE NEW ROOFING


PROVIDE SEISMIC RESTRAINTS & HOLD DOWNS FOR ALL ROOF MOUNTED EQUIPMENT & PIPING AS PER SPEC. SEC. 220548

GENERAL NOTES

- 2 ALL ROOF TOP MECHANICAL EQUIPMENT TO BE REMOVED. EXISTING MOUNTING CURBS TO BE REMOVED AND REPLACED AS PER DETAILS. WORK TO BE DONE BY LICENSED MECHANICAL CONTRACTOR. EXTEND DUCTS, CONNECTION LINES AND ELECTRICAL AS REQUIRED. REVIEW WITH OWNER PREFERRED RUBBER ISOLATION PADS UNDER UNITS.
- NEW ROOF SYSTEM = 2 LAYERS OF 2" RIGID INSULATION BD. 1 ‡" LAYER OF COVER BD. SINGLE PLY ROOFING
- NEW ROOF SYSTEM IN MECHANICAL WELL = 1 ¼" LAYER OF COVER BD. SINGLE PLY ROOFING

SOUTHERN UTAH UNIVERSIT TECH. BUILDING REROOF 351 WEST UNIVERSITY BLVD. CEDAR CITY, UTAH 84720

NEW ROOF PLAN



KEYNOTES

4 EXISTING PLYWD SHEATHING, NOTIFY ARCHITECT OF ANY LOOSE PANELS AND SECURE W/ NEW FASTENERS

9 2 LAYERS OF 2" RIGID INSULATION.

(10) EXISTING PIPE, DIAMETER VARIES

12 24 GAGE PRE FINISHED STEEL FLASHING

13 24 GAGE CONT. CLEAT FASTEN WITH 1 ½" SCREW THROUGH SLOTTED HOLES @ 24"

(14) 1 ½" SCREW FASTENER W/ NEOPRENE WASHER @ 24" O.C. - COLOR TO MATCH

16 ROOFING FASTENER AS REQUIRED BY ROOFING MFGR. LENGTH TO PENETRATE EXISTING PLYWD. SHEATHING

(17) FILL VOID W/ PLYWOOD SHEATHING STRIP

20 3 NEW 2X6 PARAPET PLATES FASTENED TOGETHER W/ 2-16D NAILS @ 24" OC - EACH PLATE, LOCATE ON ROOF AND WALL

SOLID BASE FOR NEW 2X6 PARAPET

22 NEW SINGLE PLY ROOF MEMBRANE

(24) EXISTING WOOD FRAMING

25 24 GAGE PRE-FINISHED STEEL FLASHING/FASCIA - SIZE AND SHAPE AS

27 24 GAGE G.I. FLASHING SIZE & SHAPE AS

(29) REMOVE EXISTING FASCIA PANEL TO CUT
BOTTOM UP 2" +- FOR NEW ROOFING &
PROTECTION BD. REPLACE FASCIA PANELS
AFTER ROOFING IS IN PLACE


30 PROVIDE NEW 24 GAGE G.I. FLASHING CLEAT SHAPE AS SHOWN

GENERAL NOTES

ALL ROOF TOP MECHANICAL EQUIPMENT TO BE REMOVED. EXISTING MOUNTING CURBS TO BE REMOVED AND REPLACED AS PER DETAILS. WORK TO BE DONE BY LICENSED MECHANICAL CONTRACTOR. EXTEND DUCTS, CONNECTION LINES AND ELECTRICAL AS REQUIRED. REVIEW WITH OWNER PREFERRED RUBBER ISOLATION PADS UNDER UNITS.

SOUTHERN UTAH UNIVERSITY

ROOF DETAILS



KEYNOTES (1) EXISTING LADDER TO BE REMOVED AND RE-MOUNTED WHEN NEW ROOFING IS IN PLACE (2) EXISTING WD & STEEL TRUSS

(3) EXISTING EXISTING SCREEN BEYOND

(5) EXISTING WD. JOIST @ 16" OC

(6) EXISTING PLYWD SHEATHING, NOTIFY

7) NEW SINGLE PLY ROOF MEMBRANE

9 24 GAGE PRE-FINISHED STEEL FLASHING/FASCIA - SIZE AND SHAPE AS

2 NEW 2X4 PARAPET PLATES FASTENED TOGETHER, LOCATE ON ROOF AND WALL BELOW AS SHOWN

(13) NEW TAPERED 2X6 TOP PLATE (14) ROOFING FASTENER AS REQUIRED BY ROOFING MFGR. LENGTH TO PENETRATE

EXISTING PLYWD. SHEATHING (15) EXISTING METAL SIDING FASCIA

(19) 1 ½" SCREW FASTENER W/ NEOPRENE WASHER @ 24" O.C. - COLOR TO MATCH

(21) EXISTING ROOF DRAIN

(23) NEW SECONDARY DRAIN LOCATE WHERE THE INLET IS A MAX OF 2" ABOVE THE PRIMARY

(24) 1 COVER BOARD TYP. ALL AREAS

(25) NEW LADDER W/ 2" DIA. STEEL PIPE RUNNERS AND SOLID 1" DIA. STEEL RUNGS

(26) 3 NEW 2X6 PARAPET PLATES FASTENED TOGETHER, LOCATE ON ROOF AND WALL BELOW AS SHOWN

(27) ROOFING SEAM WELD AND SEAM CAULK

(28) NEW TAPERED 2X4 TOP PLATE

29 PROVIDE CONT. CUT DOWN 2X4 AS NEEDED FOR REQUIRED HT. ABOVE INSULATION (30) PROVIDE JOINT SEALER AT ALL LAPS

31) 24 GAGE BACK UP CONNECTION PLATE AT ALL JOINTS, COLOR AND FINISH TO MATCH EXPOSED FLASHING

PROVIDE 3" HIGH STANDING SEAM JOINT ON TO OF ALL CAPS AT ALL JOINTS, TYP.

(33) TAPER SEAM BACK AT FRONT EDGE, PROVIDE TAB AT EACH END OF SEAM, TYP.

(34) 2 LAYERS OF 2" RIGID INSULATION. STAGGER ALL JOINTS

35) ADD 3/8" PLYWOOD STRIP TO PROVIDE A

36) 4X4 WD SUPPORT, POSITION OVER AT LEAST 2— TRUSSES, FASTEN TO NEW 2X4 BLOCK BELOW PLYWD W/ 4 INSET $\frac{1}{2}$ " THRU BOLTS

JOINTS, LOCATE AND SHAPE AS SHOWN, LOCATE UNDER FINISH COLORED FLASHING. PROVIDE CONT. SEALANT AT ALL LAPS (38) EXISTING WD BLOCKING LADDER SUPPORT, REPLACE BLOCKING IF REQUIRED FOR SOLID

(39) TRIM EXISTING METAL SCREEN AS REQD FOR NEW WALL CAP HT.

PROVIDE NEW 2X6 BLOCK UNDER PLYWD ROOF SHEATHING. SET BETWEEN 2 TOP TRUSS CORDS AND SECURE IN PLACE WITH SIMPSON Z4 CLIPS AT EACH END. SLIP CLIP UNDER BETWEEN PYLWD & TRUSS AND

PROVIDE DRAIN EXTENSION TO RAISE DRAIN TO NEW HT W/ NEW INSULATION


(43) WELD 2" LADDER PIPE TO A 3" X 7" X 3" BASE PLATE W/ 2 HOLES FOR ½" X 4" LAG

SUBMITTAL

3/22/2010

010001


ROOF DETAILS





ERSITY Rever

ROOF DETAILS



SOUTHERN UTAH UNIVERSITY TECH. BUILDING REROOF 351 WEST UNIVERSITY BLVD. CEDAR CITY, UTAH 84720

3/22/2010

ROOF DRAINAGE PLAN

SHEET NO.